

Cable gland DKV-MS-E (nickel plated brass)

For screened cables, EMC



Material:

- Water resistant
- Case: brass, nickel plated
- Clamping insert: polyamid
- Sealing ring: perbunan
- O-ring: perbunan

Protection type:

IP 68 – pressure 10 bars according to EN 60529

Temperature range:

-40 °C to +100 °C; short time up to +120 °C

Application:

Machine construction, plant construction, switchboard construction, automation technology. Earth cable gland is specify for shielding conduction where is required electromagnetic compatibility.

Note:

Technical changes reserved.
Further types on request.

Part No.	PG size	Ø cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1090423	7	3 - 6,5	5	14	50
1090424	9	4 - 8	6	17	50
1090425	11	5 - 10	6	20	50
1090426	13,5	6 - 12	6,5	22	50
1090427	16	10 - 14	6,5	24	50
1090428	21	13 - 18	7	30	50
1090429	29	18 - 25	8	40	25
1090430	36	22 - 32	8	50	10
1090431	42	32 - 38	9	57	5
1090432	48	37 - 44	10	64	5

Part No.	Metric size	Ø cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1097335	M12 × 1,5	3 - 6,5	5	14	50
1097336	M16 × 1,5	5 - 10	6	20	50
1097337	M20 × 1,5	10 - 14	6	24	50
1097338	M25 × 1,5	13 - 18	7	30	25
1097339	M32 × 1,5	18 - 25	8	40	10
1097340	M40 × 1,5	22 - 32	8	50	5