

Cable gland DKV-MS-EX (nickel plated brass)

For hazardous areas with possibility of explosion



Material:

- Water resistant
- Case: brass, nickel plated
- Clamping insert: polyamid
- Sealing ring: perbunan
- O-ring: perbunan

Protection type:

IP 68 – pressure 10 bars according to EN 60529

Temperature range:

-40 °C to +100 °C; short time up to +120 °C

Application:

Machine construction, plant construction, switchboard construction, automation technology.

EExe II KEMA No. Ex-91.C.9658; is suitable for hazardous areas with possibility of explosion according to DIN-EN 50014 a DIN-EN 50019.

Note:

Technical changes reserved.
Further types on request.

Part No.	PG size	Ø cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1090200	7	3 - 6,5	5	14	50
1090201	9	4 - 8	6	17	50
1090202	11	5 - 10	6	20	50
1090203	13,5	6 - 12	6,5	22	50
1090204	16	10 - 14	6,5	24	50
1090205	21	13 - 18	7	30	50
1090206	29	18 - 25	8	40	25
1090207	36	22 - 32	8	50	1
1090208	42	32 - 38	9	57	1
1090209	48	37 - 44	10	64	1

Part No.	Metric size	Ø cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1098045	M12 × 1,5	3 - 6,5	5	14	50
1098046	M16 × 1,5	4 - 8	6	17	50
1098047	M16 × 1,5	5 - 10	6	17	50
1098048	M20 × 1,5	6 - 12	6	22	50
1098049	M20 × 1,5	10 - 14	6	24	50
1098050	M25 × 1,5	13 - 18	7	30	25
1098051	M32 × 1,5	18 - 25	8	40	25
1098052	M40 × 1,5	22 - 32	8	50	10
1098053	M50 × 1,5	32 - 38	9	57	5
1098054	M63 × 1,5	37 - 44	10	68	5