

Cable gland DKV-INOX (stainless steel)



Material:

- Case: stainless steel 1.4305
- Clamping insert: polyamid
- Sealing ring: perbunan
- O-ring: perbunan

Protection type:

IP 68 – pressure 10 bars according to EN 60529

Temperature range:

-40 °C to +100 °C; short time up to +120 °C

Application:

In food industry.

Note:

Technical changes reserved.
Further types on request.



Part No.	PG size	∅ cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1090210	7	3 - 6,5	5	14	10
1090211	7	2 - 5	5	14	10
1090212	9	4 - 8	6	17	10
1090213	9	2 - 6	6	17	10
1090214	11	5 - 10	6	22	10
1090215	11	3 - 7	6	22	10
1090216	13,5	6 - 12	6,5	22	10
1090217	13,5	5 - 9	6,5	22	10
1090218	16	10 - 14	6,5	24	10
1090219	16	7 - 12	6,5	24	10
1090377	21	13 - 18	7	30	10
1090378	21	9 - 16	7	30	10
1098286	29	18 - 25	8	41	5
1098287	29	13 - 20	8	41	5
1098288	36	22 - 32	8	50	5
1098289	36	20 - 26	8	50	5

Part No.	Metric size	∅ cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1098076	M12 × 1,5	3 - 6,5	5	14	10
1098077	M12 × 1,5	2 - 5	5	14	10
1098078	M16 × 1,5	5 - 10	8	20	10
1098079	M16 × 1,5	3 - 7	8	20	10
1098080	M20 × 1,5	9 - 14	6	24	10
1098081	M20 × 1,5	7 - 12	6	24	10
1098082	M25 × 1,5	13 - 18	7	30	10
1098083	M25 × 1,5	9 - 16	7	30	10
1098084	M32 × 1,5	17 - 25	8	41	5
1098085	M32 × 1,5	13 - 20	8	41	5
1098086	M40 × 1,5	24 - 33	8	50	5
1098087	M40 × 1,5	20 - 26	8	50	5