

Cable gland DKV-MS (nickel plated brass)



Material:

- Water resistant
- Case: brass, nickel plated
- Clamping insert: PA 6 GFK
- Sealing ring: perbunan
- O-ring: perbunan

Protection type:

IP 68 – pressure 10 bars according to EN 60529

Temperature range:

-40 °C to +100 °C; short time up to +120 °C

Application:

Machine construction, plant construction, switchboard construction, automation technology.

Note:

Technical changes reserved.
Further types on request.

Part No.	PG size	Ø cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1090300	7	3 - 6,5	5	14	50
1090301	9	4 - 8	6	17	50
1090302	11	5 - 10	6	20	50
1090303	13,5	6 - 12	6,5	22	50
1090304	16	10 - 14	6,5	24	50
1090305	21	13 - 18	7	30	50
1090306	29	18 - 25	8	40	25
1090307	36	22 - 32	8	50	1
1090308	42	32 - 38	9	57	1
1090309	48	37 - 44	10	64	1

Part No.	Metric size	Ø cable [mm]	Thread length [mm]	Nut width [mm]	Min. packing [pc]
1098285	M12 × 1,5	3 - 6,5	5	14	50
1090292	M16 × 1,5	4 - 8	5	17	50
1098033	M16 × 1,5	5 - 10	6	20	50
1090293	M20 × 1,5	6 - 12	6	22	50
1098034	M20 × 1,5	10 - 14	6	24	50
1090294	M25 × 1,5	13 - 18	7	30	50
1090295	M32 × 1,5	18 - 25	8	40	25
1090296	M40 × 1,5	22 - 32	8	50	10
1090297	M50 × 1,5	32 - 38	9	57	5
1090298	M63 × 1,5	37 - 44	10	68	5