

Copper braided hose



Material:

tinned copper

Temperature range:

cca -75 °C up to +150 °C

Application:

Serves as a shielding and anti-interference drogue for pulling the cable as well as a filler. Further more, it can be used as a braiding for metal, PVC, rubber and high pressure hoses and cables.

Note:

Technical changes reserved.
Further types on request.

Characteristics:

- Highly flexible braiding
- Overthrust in axial direction. Thereby is facilitated putting on of hose
- This braided hose makes higher tensile strength and inner pressure strength
- Optimal surface covering

Part No.	Nominal size [mm]	Max. Ø cable [mm]	Min. Ø cable [mm]	Min. packing [m]
1097397	6	12	5	100
1097399	10	17	8	50
1097400	15	22	12	50
1097402	20	27	16	50
1097403	25	35	20	25

Galvanised steel braided hose

Material:

galvanised steel

Temperature range:

up to approx. +300 °C

Application:

This hose is suitable for mechanical protection of cables, wires and tubes.

Note:

Technical changes reserved.
Further types on request.

Part No.	Nominal size [mm]	Max. Ø cable [mm]	Min. Ø cable [mm]	Min. packing [m]
1097197	6	12	5	100
1097199	10	17	8	50
1097200	15	22	12	50
1097202	20	27	16	50
1096561	25	35	20	50